BUILT FOR LIFE

RELIABILITY

CAPABILITY

DURABILITY



Single Cab Specifications:

ISUZU D-MAX 250C SINGLE CAB STANDARD GEN 6



ISUZU D-MAX 250C SINGLE CAB STANDARD GEN 6

ENGINE	
Engine Code	4JA1-L
Displacement (cc)	2 499
No. of Cylinders	4
Compression Ratio	18.5:1
Bore x Stroke (mm)	93 x 92
No. of Valves	8
Power (kW) @ r/min	58 @ 3 900
Torque (nm) @ r/min	176 @ 1 800
Turbocharger	Standard
Intercooler	-

FUEL CONSUMPTION ¹	
Combined Cycle (L/100 km)	7,9
Combined Co ₂ Emissions (g/km)	208
Fuel Type	Diesel

Transmission Type	5-Speed Manua
Gear Ratio: 1st	4,008
Gear Ratio: 2nd	2,301
Gear Ratio: 3rd	1,427
Gear Ratio: 4th	1
Gear Ratio: 5th	0,744
Gear Ratio: 6th	-
Gear Ratio: Reverse	3,651
4WD Selector	-
Low Range Ratio	-

FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km/h	-
Axle Ratio: Final Drive	-

REAR DIFFERENTIAL	
Differential Lock	-
Axle Ratio: Final Drive	4,555

CHASSIS DESIGN	
Wheel Suspension Front	Coil Over Shock
Wheel Suspension Rear	Leaf Spring Underslung
Shock Absorbers	Twintube Gas Pressurised (Heavy Duty)
Suspension	Low-Ride
Skid Plate Guard	Standard
Engine Sump Guard	-
Transfer Case Guard	-

WHEELS AND TYRES	
Tyre Size	215 / 70 R16 C
Wheel Type and Size	16" x 6.5J-41 Steel
Spare Wheel	16" x 6.5J-41 Steel
Turning Circle: Curb-To-Curb (m)	12,2

Length (mm)	5 218
Width (mm)	1 860
Height (mm)	1 690
Wheelbase (mm)	3 095
Track Front / Rear (mm)	1 510 / 1 510
Rear Overhang (mm)	1 225
Ground Clearance (mm)	200
Loadbox Length (mm)	2 305
Loadbox Width (mm)	1 535
Loadbox Depth (mm)	445
Approach Angle (°)	21
Departure Angle (°)	17,2
Breakover Angle (°)	17,6
Wading Depth (mm)	400

MASS / CAPACITY	
Gross Axle Mass – Front (GA1) (kg)	1 250
Gross Axle Mass – Rear (GA2) (kg)	1 870
Gross Vehicle Mass (GVM) (kg)	2 850
Gross Combined Mass (GCM) (kg)	4 450
Tare Mass (kg)	1 615
Payload (kg)	1 176
Towing Capacity (kg): Unbraked ²	750
Towing Capacity (kg): Braked ²	1 600
Fuel Tank Capacity (L)	80

LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
Rope Hooks on Loadbox Side	Standard

SAFETY FEATURES	
Load-Sensing Proportioning Valve (LSPV)	Standard
Anti-Lock Braking System (ABS)	-
Electronic Brake-Force Distribution (EBD)	-
Brake-Assist System (BAS)	_
Electronic Stability Control (ESC) with Traction Control	-
Hill-Start Assist (HSA)	-
Hill Descent Control (HDC)	-
Trailer Sway Control	_
Brake Override System (BOS)	-
Height-Adjustable 3-Point Front Seatbelts	Standard
Front Seat Centre Lap Belt (2 Point)	Standard
Seatbelt Pre-Tensioners	Standard
Fixed 3-Point Rear Seatbelts	-
Seatbelt Reminder	Driver
Driver and Passenger Airbags	Standard
Front Seat Side Airbags	-
Curtain Airbags	_
Side-Impact Protection Bars	Standard
Collapsible Steering Column	Standard
Speed-Sensitive Door Lock	-
ISOFIX Child-Seat Attachment	-
Parking Distance Sensors	-
Rear-View Camera	-
Warning Triangle Kit	Standard

SECURITY FEATURES	
Manual Door Locks	Standard
Remote-Controlled Central Locking	-
Remote Keyless Entry	-
Passive Entry Start System (PESS)	-
Child-Proof Rear Door Locks	-
Anti-Theft Alarm System	Alarm Ready
Ultrasonic Alarm	-
Transponder Immobiliser System	Standard

INTERIOR / EXTERIOR LIGHTING	
Front Reading Lamps	-
Interior Courtesy Lamp	Standard
Illuminated Entry	-
Front Fog Lamps	-
Daytime Running Lights (DRL)	-
Headlamps	Halogen
Headlamp Levelling	-
Headlamps "ON" Warning Buzzer	Standard
Turn Indicator Lamp on Door	Standard
Rear Tail Lamps – Combination	Bulb
High-Mounted Centre Stop Lamp	Standard

EXTERIOR FEATURES	
Front Wiper	Intermittent
Radiator Grille	Grey
Front Bumper	Black
Front Fog Lamp Garnish	-
Rear Bumper	-
Towbar	-
Exterior Door Handle	Black
Exterior Mirror	Black – Manual Adjustment
B-Pillar Blackout	-
Roof Rails	-
Sports Bar	-
Side-Steps	-
Mudflaps	Front and Rear
Tailgate Handle	Body Colour

Hydraulic
-
-
Day / Night
Driver And Passenger

and Sunglasses Holder	
Digital Clock	Standard
Cruise Control	-
Multi-Information Display (MID)	-
Dashboard Illumination Control	Standard
Power Socket – Auxiliary 12V IP Mounted	1
Cigarette Lighter	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard
Steering Column Adjustment	Tilt
Steering Wheel Trim	Urethane
Steering Wheel Multi-Functional Controls	-
Gear Shift Trim	Standard
Front Seat Configuration	60:40-Split Bench Cushion
Rear Seat Configuration	-
Seat Trim	Canvas
Seat Adjustment	4-Way Manual Driver
Storage Pockets behind Front Seats	-
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Interior Door Release Handle	Black
Interior Trim Colours	Light Grey Upper / Dark Grey Lower
A-Pillar Assist Grip, Driver and Passenger	-
Roof-Mounted Assist Grips	Passenger
Floor Trim	Vinyl with Heel Mat (x2)
Floor Tunnel Console with Integrated Cupholder	-
Centre Console Storage Box with Lid	-
Driver Footrest	Standard
Rear Heater Duct	-
Storage Box	-
Window Operation	Manual Front
Rear Window	Fixed without Defogge
Fuel Flap Remote Opener	Standard

INFOTAINMENT	
Audio System	Optional
Audio Input Terminal: USB, Auxiliary, iPod	-
USB Port (Music Playback and Device Link)	-
USB Charge Port	-
Speakers	Optional (x2)
Antenna	-

Differential Lock	_
16" Alloy Wheel and 205 R16 C Tyre	
(All Terrain)	
16" Alloy Wheel and 245 / 70 R16 Tyre (All Terrain)	-
18" Silver Diamond Cut Alloy Wheel and 255 / 60 R18 Tyre (All Terrain)	-
18" All Black Alloy Wheel and 255 / 60 R18 Tyre (All Terrain)	-
Front Bumper – Body Coloured	Available
Sliding Rear Window	Available
Fixed Rear Window without Defogger	-
Fixed Rear Window with Defogger	-
Partial Leather Seats – Black with Driver 6-Way Manual Adjustment	-
Partial Leather Seats – Black with Driver 6-Way Power Adjustment	-
AM/FM Radio, CD Player, USB, Clock, Bluetooth® – Audio Streaming and Handsfree Phone	Available
AM/FM Radio, 8" Touchscreen, Bluetooth® – Audio Streaming and Handsfree Phone	-
AM/FM Radio, 9" Touchscreen, Bluetooth [®] – Audio Streaming and Handsfree Phone, Navigation	-
Speakers	2
Antenna – Roof GPS	Available
Roof Rails – Silver	_
Roof Rails – Black	-
Metallic Paint	Available
Sports Bar – Black	_
Sports Bar – Chrome	-

WARRANTY AND SERVICE INTERVALS	
Warranty and Roadside Assistance	5 Years / 120 000 km
Anti-Corrosion Warranty	5 Years / Unlimited km
Service Plan	5 Years / 90 000 km
Service Intervals	12 Months / 15 000 km

 $^{^{1}}$ Fuel Economy and CO_2 data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

² Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded (e.g.: if a 3.0 L Diesel is towing 3 500 kg, its maximum vehicle mass is 2 500 kg in order to be within GCM). Date of print April 2022.

BUILT FOR LIFE

RELIABILITY

CAPABILITY

DURABILITY



Single Cab Specifications:

ISUZU D-MAX 250C SINGLE CAB FLEETSIDE GEN 6



ISUZU D-MAX 250C SINGLE CAB FLEETSIDE GEN 6

ENGINE	
Engine Code	4JA1-L
Displacement (cc)	2 499
No. of Cylinders	4
Compression Ratio	18.5:1
Bore x Stroke (mm)	93 x 92
No. of Valves	8
Power (kW) @ r/min	58 @ 3 900
Torque (nm) @ r/min	176 @ 1 800
Turbocharger	Standard
Intercooler	-

FUEL CONSUMPTION ¹	
Combined Cycle (L/100 km)	7,9
Combined Co ₂ Emissions (g/km)	208
Fuel Type	Diesel

TRANSMISSION	
Transmission Type	5-Speed Manual
Gear Ratio: 1st	4,008
Gear Ratio: 2nd	2,301
Gear Ratio: 3rd	1,427
Gear Ratio: 4th	1
Gear Ratio: 5th	0,744
Gear Ratio: 6th	-
Gear Ratio: Reverse	3,651
4WD Selector	-
Low Range Ratio	-

FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km/h	-
Axle Ratio: Final Drive	-

REAR DIFFERENTIAL	
Differential Lock	-
Axle Ratio: Final Drive	4,555

Wheel Suspension Front	Coil Over Shock
Wheel Suspension Rear	Leaf Spring Underslung
Shock Absorbers	Twintube Gas Pressurised (Heavy Duty)
Suspension	High-Ride
Skid Plate Guard	Standard
Engine Sump Guard	Standard
Transfer Case Guard	-

WHEELS AND TYRES	
Tyre Size	205 R16 C
Wheel Type and Size	Steel 16" x 6.5J-33
Spare Wheel	Steel 16" x 6.5J-33
Turning Circle: Curb-To-Curb (m)	12.8

DIMENSIONS	
Length (mm)	5 218
Width (mm)	1 860
Height (mm)	1 790
Wheelbase (mm)	3 095
Track Front / Rear (mm)	1 570 / 1 570
Rear Overhang (mm)	1 225
Ground Clearance (mm)	225
Loadbox Length (mm)	2 305
Loadbox Width (mm)	1 535
Loadbox Depth (mm)	445
Approach Angle (°)	30
Departure Angle (°)	22,4
Breakover Angle (°)	22,4
Wading Depth (mm)	600

MASS / CAPACITY	
Gross Axle Mass – Front (GA1) (kg)	1 350
Gross Axle Mass – Rear (GA2) (kg)	1 870
Gross Vehicle Mass (GVM) (kg)	2 850
Gross Combined Mass (GCM) (kg)	4 450
Tare Mass (kg)	1 660
Payload (kg)	1 131
Towing Capacity (kg): Unbraked ²	750
Towing Capacity (kg): Braked ²	1 600
Fuel Tank Capacity (L)	80

LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
Rope Hooks on Loadbox Side	Standard

SAFETY FEATURES	
Load-Sensing Proportioning Valve (LSPV)	Standard
Anti-Lock Braking System (ABS)	-
Electronic Brake-Force Distribution (EBD)	-
Brake-Assist System (BAS)	-
Electronic Stability Control (ESC) with Traction Control	-
Hill-Start Assist (HSA)	-
Hill Descent Control (HDC)	-
Trailer Sway Control	-
Brake Override System (BOS)	-
Height-Adjustable 3-Point Front Seatbelts	Standard
Front Seat Centre Lap Belt (2 Point)	Standard
Seatbelt Pre-Tensioners	Standard
Fixed 3-Point Rear Seatbelts	-
Seatbelt Reminder	Driver
Driver and Passenger Airbags	Standard
Front Seat Side Airbags	-
Curtain Airbags	-
Side-Impact Protection Bars	Standard
Collapsible Steering Column	Standard
Speed-Sensitive Door Lock	-
ISOFIX Child-Seat Attachment	-
Parking Distance Sensors	-
Rear-View Camera	-
Warning Triangle Kit	Standard

SECURITY FEATURES	
Manual Door Locks	Standard
Remote-Controlled Central Locking	-
Remote Keyless Entry	-
Passive Entry Start System (PESS)	-
Child-Proof Rear Door Locks	-
Anti-Theft Alarm System	Alarm Ready
Ultrasonic Alarm	-
Transponder Immobiliser System	Standard

INTERIOR / EXTERIOR LIGHTING	
Front Reading Lamps	-
Interior Courtesy Lamp	Standard
Illuminated Entry	-
Front Fog Lamps	-
Daytime Running Lights (DRL)	-
Headlamps	Halogen
Headlamp Levelling	-
Headlamps "ON" Warning Buzzer	Standard
Turn Indicator Lamp on Door	Standard
Rear Tail Lamps – Combination	Bulb
High-Mounted Centre Stop Lamp	Standard

Front Wiper	Intermittent
Radiator Grille	Grey
Front Bumper	Black
Front Fog Lamp Garnish	-
Rear Bumper	-
Towbar	-
Exterior Door Handle	Black
Exterior Mirror	Black – Manua Adjustment
B-Pillar Blackout	-
Roof Rails	-
Sports Bar	-
Side-Steps	-
Mudflaps	Front and Rear
Tailgate Handle	Body Colour

INTERIOR FEATURES	
Power-Assisted Steering (PAS)	Hydraulic
Air-Conditioner	Manual
Pollen Filter	Standard
Inside Rear-View Mirror	Day / Night
Sunvisor	Driver And Passenger

Overhead Console with Map Lamps (x2) and Sunglasses Holder	-
Digital Clock	Standard
Cruise Control	-
Multi-Information Display (MID)	-
Dashboard Illumination Control	Standard
Power Socket – Auxiliary 12V IP Mounted	1
Cigarette Lighter	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard
Steering Column Adjustment	Tilt
Steering Wheel Trim	Urethane
Steering Wheel Multi-Functional Controls	-
Gear Shift Trim	Standard
Front Seat Configuration	60:40-Split Bench Cushion
Rear Seat Configuration	-
Seat Trim	Canvas
Seat Adjustment	4-Way Manual Driver
Storage Pockets behind Front Seats	-
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Interior Door Release Handle	Black
Interior Trim Colours	Light Grey Upper / Dark Grey Lower
A-Pillar Assist Grip, Driver and Passenger	Standard
Roof-Mounted Assist Grips	Passenger
Floor Trim	Vinyl with Heel Mat (x2)
Floor Tunnel Console with Integrated Cupholder	-
Centre Console Storage Box with Lid	-
Driver Footrest	Standard
Rear Heater Duct	-
Storage Box	-
Window Operation	Manual Front
Rear Window	Fixed without Defogge
Fuel Flap Remote Opener	Standard

INFOTAINMENT	
Audio System	Optional
Audio Input Terminal: USB, Auxiliary, iPod	-
USB Port (Music Playback and Device Link)	-
USB Charge Port	-
Speakers	Optional (x2)
Antenna	-

OPTIONS	
Differential Lock	-
16" Alloy Wheel and 205 R16 C Tyre (All Terrain)	Available
16" Alloy Wheel and 245 / 70 R16 Tyre (All Terrain)	-
18" Silver Diamond Cut Alloy Wheel and 255 / 60 R18 Tyre (All Terrain)	-
18" All Black Alloy Wheel and 255 / 60 R18 Tyre (All Terrain)	-
Front Bumper – Body Coloured	Available
Sliding Rear Window	Available
Fixed Rear Window without Defogger	_
Fixed Rear Window with Defogger	_
Partial Leather Seats – Black with Driver 6-Way Manual Adjustment	-
Partial Leather Seats – Black with Driver 6-Way Power Adjustment	-
AM/FM Radio, CD Player, USB, Clock, Bluetooth® - Audio Streaming and Handsfree Phone	Available
AM/FM Radio, 8" Touchscreen, Bluetooth® – Audio Streaming and Handsfree Phone	-
AM/FM Radio, 9" Touchscreen, Bluetooth [®] - Audio Streaming and Handsfree Phone, Navigation	-
Speakers	2
Antenna – Roof GPS	Available
Roof Rails – Silver	-
Roof Rails – Black	-
Metallic Paint	Available
Sports Bar – Black	-
Sports Bar – Chrome	_

WARRANTY AND SERVICE INTERVALS	
Warranty and Roadside Assistance	5 Years / 120 000 km
Anti-Corrosion Warranty	5 Years / Unlimited km
Service Plan	5 Years / 90 000 km
Service Intervals	12 Months / 15 000 km

 $^{^{1}}$ Fuel Economy and CO_2 data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

² Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded (e.g.: if a 3.0 L Diesel is towing 3 500 kg, its maximum vehicle mass is 2 500 kg in order to be within GCM). Date of print April 2022.

BUILT FOR LIFE

RELIABILITY

CAPABILITY

DURABILITY



Single Cab Specifications:

ISUZU D-MAX 250 HO SINGLE CAB FLEETSIDE SAFETY GEN 6



ISUZU D-MAX 250 HO SINGLE CAB FLEETSIDE SAFETY GEN 6

ENGINE	
Engine Code	4JK1-TC HO
Displacement (cc)	2 499
No. of Cylinders	4
Compression Ratio	18.1:1
Bore x Stroke (mm)	95.4 x 87.4
No. of Valves	16
Power (kW) @ r/min	100 @ 3 400
Torque (nm) @ r/min	320 @ 1 800 - 2 800
Turbocharger	Standard
Intercooler	Standard

FUEL CONSUMPTION ¹	
Combined Cycle (L/100 km)	7,6
Combined Co₂ Emissions (g/km)	199
Fuel Type	Diesel

TRANSMISSION	
Transmission Type	5-Speed Manua
Gear Ratio: 1st	4,008
Gear Ratio: 2nd	2,301
Gear Ratio: 3rd	1,427
Gear Ratio: 4th	1
Gear Ratio: 5th	0,744
Gear Ratio: 6th	-
Gear Ratio: Reverse	3,651
4WD Selector	-
Low Range Ratio	-

FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km/h	-
Axle Ratio: Final Drive	-

REAR DIFFERENTIAL	
Differential Lock	-
Axle Ratio: Final Drive	4,1

CHASSIS DESIGN	
Wheel Suspension Front	Coil Over Shock
Wheel Suspension Rear	Leaf Spring Overslung
Shock Absorbers	Twintube Gas Pressurised (Heavy Duty)
Suspension	High-Ride
Skid Plate Guard	Standard
Engine Sump Guard	Standard
Transfer Case Guard	-

WHEELS AND TYRES	
Tyre Size	245 / 70R 16 C
Wheel Type and Size	Steel 16" x 6.5J-33
Spare Wheel	Steel 16" x 6.5J-33
Turning Circle: Curb-To-Curb (m)	12,8

DIMENSIONS	
Length (mm)	5 218
Width (mm)	1 860
Height (mm)	1 790
Wheelbase (mm)	3 095
Track Front / Rear (mm)	1 570 / 1 570
Rear Overhang (mm)	1 225
Ground Clearance (mm)	225
Loadbox Length (mm)	2 305
Loadbox Width (mm)	1 535
Loadbox Depth (mm)	445
Approach Angle (°)	30
Departure Angle (°)	22,4
Breakover Angle (°)	22,4
Wading Depth (mm)	600

Gross Axle Mass – Front (GA1) (kg)	1 350
Gross Axle Mass – Rear (GA2) (kg)	1 870
Gross Vehicle Mass (GVM) (kg)	3 000
Gross Combined Mass (GCM) (kg)	5 000
Tare Mass (kg)	1 710
Payload (kg)	1 231
Towing Capacity (kg): Unbraked ²	750
Towing Capacity (kg): Braked ²	2 100
Fuel Tank Capacity (L)	80

LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
Rope Hooks on Loadbox Side	Standard

SAFETY FEATURES	
Load-Sensing Proportioning Valve (LSPV)	-
Anti-Lock Braking System (ABS)	Standard
Electronic Brake-Force Distribution (EBD)	Standard
Brake-Assist System (BAS)	Standard
Electronic Stability Control (ESC) with Traction Control	Standard
Hill-Start Assist (HSA)	Standard
Hill Descent Control (HDC)	Standard
Trailer Sway Control	-
Brake Override System (BOS)	-
Height-Adjustable 3-Point Front Seatbelts	Standard
Front Seat Centre Lap Belt (2 Point)	Standard
Seatbelt Pre-Tensioners	Standard
Fixed 3-Point Rear Seatbelts	-
Seatbelt Reminder	Driver
Driver and Passenger Airbags	Standard
Front Seat Side Airbags	-
Curtain Airbags	-
Side-Impact Protection Bars	Standard
Collapsible Steering Column	Standard
Speed-Sensitive Door Lock	-
ISOFIX Child-Seat Attachment	-
Parking Distance Sensors	-
Rear-View Camera	-
Warning Triangle Kit	Standard

SECURITY FEATURES		
Manual Door Locks	Standard	
Remote-Controlled Central Locking	-	
Remote Keyless Entry	-	
Passive Entry Start System (PESS)	-	
Child-Proof Rear Door Locks	-	
Anti-Theft Alarm System	Alarm Ready	
Ultrasonic Alarm	-	
Transponder Immobiliser System	Standard	

INTERIOR / EXTERIOR LIGHTING	
Front Reading Lamps	-
Interior Courtesy Lamp	Standard
Illuminated Entry	-
Front Fog Lamps	-
Daytime Running Lights (DRL)	-
Headlamps	Halogen
Headlamp Levelling	-
Headlamps "ON" Warning Buzzer	Standard
Turn Indicator Lamp on Door	Standard
Rear Tail Lamps – Combination	Bulb
High-Mounted Centre Stop Lamp	Standard

Front Wiper	Intermittent	
Radiator Grille	Grey	
Front Bumper	Black	
Front Fog Lamp Garnish	-	
Rear Bumper	-	
Towbar	-	
Exterior Door Handle	Black	
Exterior Mirror	Black – Manua Adjustment	
B-Pillar Blackout	-	
Roof Rails	-	
Sports Bar	-	
Side-Steps	-	
Mudflaps	Front and Rear	
Tailgate Handle	Body Colour	

INTERIOR FEATURES		
Power-Assisted Steering (PAS)	Hydraulic	
Air-Conditioner	Manual	
Pollen Filter	Standard	
Inside Rear-View Mirror	Day / Night	
Sunvisor	Driver And Passenger	

Overhead Console with Map Lamps (x2) and Sunglasses Holder	-
Digital Clock	Standard
Cruise Control	-
Multi-Information Display (MID)	-
Dashboard Illumination Control	Standard
Power Socket – Auxiliary 12V IP Mounted	1
Cigarette Lighter	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard
Steering Column Adjustment	Tilt
Steering Wheel Trim	Urethane
Steering Wheel Multi-Functional Controls	-
Gear Shift Trim	Standard
Front Seat Configuration	60:40-Split Bench Cushion
Rear Seat Configuration	-
Seat Trim	Canvas
Seat Adjustment	4-Way Manual Driver
Storage Pockets behind Front Seats	-
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Interior Door Release Handle	Black
Interior Trim Colours	Light Grey Upper / Dark Grey Lower
A-Pillar Assist Grip, Driver and Passenger	Standard
Roof-Mounted Assist Grips	Passenger
Floor Trim	Vinyl With Heel Mat (x2)
Floor Tunnel Console with Integrated Cupholder	-
Centre Console Storage Box with Lid	-
Driver Footrest	Standard
Rear Heater Duct	-
Storage Box	-
Window Operation	Manual Front
Rear Window	Fixed without Defogge
Fuel Flap Remote Opener	Standard

INFOTAINMENT	
Audio System	Optional
Audio Input Terminal: USB, Auxiliary, iPod	-
USB Port (Music Playback and Device Link)	-
USB Charge Port	-
Speakers	Optional (x2)
Antenna	-

Differential Lock	-
6" Alloy Wheel and 205 R16 C Tyre All Terrain)	-
6" Alloy Wheel and 245 / 70 R16 Tyre All Terrain)	Available
8" Silver Diamond Cut Alloy Wheel and 255 / 60 R18 Tyre (All Terrain)	-
8" All Black Alloy Wheel and 255 / 60 R18 'yre (All Terrain)	-
ront Bumper – Body Coloured	Available
iliding Rear Window	Available
ixed Rear Window without Defogger	-
ixed Rear Window with Defogger	-
Partial Leather Seats – Black with Driver 5-Way Manual Adjustment	-
Partial Leather Seats – Black with Driver 5-Way Power Adjustment	-
M/FM Radio, CD Player, USB, Clock, Bluetooth® - Audio Streaming and Handsfree Phone	Available
AM/FM Radio, 8" Touchscreen, Bluetooth® – Audio Streaming and Handsfree Phone	-
M/FM Radio, 9" Touchscreen, Bluetooth® Audio Streaming and Handsfree Phone, Navigation	-
peakers	2
Intenna – Roof GPS	Available
Roof Rails – Silver	-
loof Rails – Black	-
Metallic Paint	Available
ports Bar – Black	-
ports Bar – Chrome	_

WARRANTY AND SERVICE INTERVALS	
Warranty and Roadside Assistance	5 Years / 120 000 km
Anti-Corrosion Warranty	5 Years / Unlimited km
Service Plan	5 Years / 90 000 km
Service Intervals	12 Months / 15 000 km

 $^{^{1}}$ Fuel Economy and CO_2 data as per ECE R101 / SANS 20101 Regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

² Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded (e.g.: if a 3.0 L Diesel is towing 3 500 kg, its maximum vehicle mass is 2 500 kg in order to be within GCM). Date of print April 2022.